

DATA SHEET – 476 SD 9B

MODEL	TENSION	POWER RATING	CONSUMPTION	AMPERE	FREQUENCY
Warmer Humidity Non Merchandiser, 9 trays	120V	702W	0.702 Kwh	5.85 A	50-60 Hz
Warmer Humidity Non Merchandiser SS, 9 trays	120V	702W	0.702 Kwh	5.85 A	50-60 Hz
Warmer Humidity Non Merchandiser PT, 9 trays	120V	702W	0.702 Kwh	5.85 A	50-60 Hz

SS = Selv-Service / PT = Pass-Thru

GENERAL FEATURES:

- > Brushed stainless steel 439/441, 0.5mm thick and bright stainless steel 430, 1mm thick;
- > Bright stainless steel 430, 0.4mm thick trays;
- > Carbon steel nickel-plated grill;
- > 4mm thick tempered glass;
- > Anodized aluminum frame in matte gray;
- > Maximum energy consumption of 0.702 Kwh;
- > 700W tubular resistance;
- > Capillary thermostat (86°F - 203°F);
- > Analog thermometer;
- > Fiberglass wire 18 AWG max. temp. 842°F;
- > LED light 12V IP20 4.8W/M;
- > Electric cable 18AWG American plug NEMA 5-15P;

SIZE	VOLUME (inner)	NET WEIGHT	PACKAGE	VOLUME (outer)	GROSS WEIGHT
18" x 17.5" x 28.3"	2874.19 oz	41.9 lb	20.3" x 19.3" x 35.9"	14065.261 in ³	49 lb

