





CLEARANCE REQUIREMENTS

	LEFT / RIGHT: 6" (150MM)	BACK: 0" (0MM)
	IMPORTANT: Do not cover side vents of m	nachine. Machine requires adequate spa-
cing for proper ventilation. Lack of ventilation can damage the condenser, com-		
	pressor and other components and doing s	so could lead to warranty being voided.

ELECTRICAL (CORD AND PLUG INCLUDED, DEDICATED CIRCUIT REQUIRED)

ELECTRICATE (CORD AND I EGG INGEODED, DEDIGATED GIRCOTT REGUIRED)	
VOLTAGE: 220v	PHASE: Single
HERTZ: 60	AMPS: 10A
WATTS: 1,800	AWG : 12
ENERGY CONSUMPTION: 1.8 kW/hr	

DIMENSIONS

MACHINE (LxDxH): 17.5" x 25.6/32" x 31.3"	
WEIGHT: 231 lbs. (105kg)	

SHIPPING

DIMENSIONS: 21" x 33.5" x 37.4" **WEIGHT:** 264 lbs. (120kg) **CLASS:** 70

WARNING: This product can expose you to chemicals including arsenic, which is known to the State of California to cause cancer. For more information, go to www.P65Warnings.ca.gov

ACAI MACHINE

Single Flavor Acai Berry Soft Serve Freezer

Model: AC5

Features:

- With a complete stainless-steel body this machine guarantees quality, durability all while facilitating the cleaning process of the equipment
- Produces up to 20 quarts (5 gallons) per hour
- With a production capacity of 60x 10 bowls per hour
- Batch produce up to 5x 10oz bowls in a minute
- Freezing Cylinder: One, 1.8-liter cylinder (1.9 quart)
- Mix Hopper: One, 11.6 quart (11 liters)
- All washable parts are highly durable injection molded plastic or stainless steel
- Agitator in Hopper
- Air Cooled Machine
- 1.25 HP Beater Motor
- 2x Compressors: Separate Cylinder and Hopper compressors. 3100 and 400 BTU/hr. respectively
- Operational Modes: Serve, Conservation, Cleaning/Defrost
- Texture Control
- Low Mix Indicator Lights alerts operator to add mix.
- Refrigerated Hoppers that maintain mix below 40°F (4.4°C) during Serve and Conservation modes
- During long no-use periods, the conservation feature maintains safe product temperatures in the mix hopper and freezing cylinder
- Hopper temperature is displayed to assure safe product temperatures





